

YBS *Foil Tape*

Aluminium Foil



Description:

Aluminium Foil tape coated with a long lasting, ultra violet resistant acrylic adhesive on one side, and lined with a release paper to protect the adhesive face. This product meets class 1 and class 0 fire regulations.

Uses:

A highly specified Aluminium Foil Tape for use in any situation where long life, great adhesive strength or ultra violet resistance is required.

Specification

Widths Available:	50mm - 75mm - 100mm
Standard Length:	45.7M (50 yards)
Total Thickness: Including release liner	0.120µm
Tack to Steel:	12.8 N / 25mm
Shear:	30 hours
Tensile Strength with release liner:	180 N / 25mm
Tensile Strength without release liner:	40 N / 25mm
Adhesion to Steel:	After 1 hour 18 N / 25mm After 24 hours 25 N / 25mm
Adhesion to Self:	After 1 hour 13 N / 25mm
Application Temperature:	+5° C to + 60° C (Can be applied a temps. down to 0° C as long as surface is free from ice or moisture)
Service Temperature:	-40° C to + 120° C (Can withstand up to 140° C for short periods)
Moisture Vapour Permeability:	Less than 1gm/M2/24 hrs @ 38° and 90% RH.

REF: AS291TN High Performance 30 micron Aluminium Foil Tape.

YBS Insulation

HIGH QUALITY PRODUCTS FOR THE BUILDING INDUSTRY

Yorkshire Building Services (whitwell) Ltd Crags Industrial Park, Morven Street, Creswell, Derbyshire, S80 4AJ

Tel: +44 (0) 844 99 100 44 Fax: +44 (0) 844 99 100 55

E-Mail: sales@ybsinsulation.com Web: www.ybsinsulation.com

© Yorkshire Building Services (whitwell) Ltd.